

## International Window 8920 1" Insulating Glass Unit Performance

### Sliding Door w/Steel Spacer

	U-Factors						SHGC			Visible Light		
	Air fill	With Argon	Sculptured Grid	Sculptured Grid with Argon	1/8" x 3/4"	1/8" x 3/4" Grid with Argon		Sculptured Grid	1/8" x 3/4" Grid		Sculptured Grid	1/8" x 3/4" Grid
1/8 clear/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.63	0.56	0.56	0.67	0.59	0.59
3/16 clear/ 3/16 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.60	0.53	0.53	0.66	0.58	0.58
1/8 EnergyShield™/ 1/8 clear	0.43	0.39	0.43	0.39	0.43	0.39	0.32	0.29	0.29	0.57	0.50	0.50
3/16 EnergyShield™/ 3/16 clear	0.42	0.39	0.42	0.39	0.42	0.39	0.32	0.28	0.28	0.57	0.50	0.50
1/8 EnergyShield Xtreme™/ 1/8 clear	0.43	0.39	0.43	0.39	0.43	0.39	0.24	0.21	0.21	0.51	0.45	0.45
3/16 EnergyShield Xtreme™/ 3/16 clear	0.42	0.38	0.42	0.38	0.42	0.38	0.24	0.21	0.21	0.50	0.44	0.44
1/8 bronze/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.52	0.46	0.46	0.50	0.44	0.44
3/16 bronze/ 3/16 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.46	0.41	0.41	0.43	0.38	0.38
1/4 Solarcool/ 3/16 clear	0.55	0.54	0.55	0.54	0.55	0.54	0.26	0.23	0.23	0.15	0.13	0.13
1/8 grey/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.48	0.43	0.43	0.45	0.39	0.39
3/16 grey/ 3/16 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.42	0.37	0.37	0.37	0.33	0.33
1/8 greylite # 31/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.27	0.24	0.24	0.18	0.15	0.15
1/8 Azuria/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.40	0.36	0.36	0.57	0.50	0.50
3/16 Azuria/ 3/16 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.35	0.31	0.31	0.53	0.46	0.46
1/8 bronze/ 1/8 EnergyShield™	0.43	0.39	0.43	0.39	0.43	0.39	0.32	0.28	0.28	0.43	0.37	0.37
3/16 bronze/ 3/16 EnergyShield™	0.42	0.39	0.42	0.39	0.42	0.39	0.29	0.26	0.26	0.37	0.32	0.32
1/8 grey/ 1/8 EnergyShield™	0.43	0.39	0.43	0.39	0.43	0.39	0.30	0.27	0.27	0.38	0.34	0.34
3/16 grey/ 3/16 EnergyShield™	0.42	0.39	0.42	0.39	0.42	0.39	0.26	0.24	0.24	0.32	0.28	0.28
1/8 Azuria/ 1/8 EnergyShield™	0.43	0.39	0.43	0.39	0.43	0.39	0.30	0.27	0.27	0.49	0.43	0.43
3/16 Azuria/ 3/16 EnergyShield™	0.42	0.39	0.42	0.39	0.42	0.39	0.28	0.25	0.25	0.46	0.40	0.40
3/16 Solexia/ 3/16 EnergyShield™	0.42	0.39	0.42	0.39	0.42	0.39	0.32	0.29	0.29	0.50	0.44	0.44
DS EnergyShield Xtreme™/ DS ILE	0.37	0.35	0.37	0.35	0.37	0.35	0.23	0.21	0.21	0.49	0.43	0.43
3/16 EnergyShield Xtreme™/ 3/16 ILE	0.37	0.34	0.37	0.34	0.37	0.34	0.23	0.21	0.21	0.49	0.43	0.43

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.\* ft<sup>2</sup>\*°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost

EnergyShield™ spectrally selective Low-E with emissivity 0.036

EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024

## International Window 8920 3/4" Insulating Glass Unit Performance

### Sliding Door w/Xtreme Spacer

	U-Factors						SHGC			Visible Light		
	Air fill	With Argon	Sculptured Grid	Sculptured Grid with Argon	1/8" x 3/4"	1/8" x 3/4" Grid with Argon		Sculptured Grid	1/8" x 3/4" Grid		Sculptured Grid	1/8" x 3/4" Grid
1/8 clear/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.63	0.56	0.56	0.67	0.59	0.59
3/16 clear/ 3/16 clear	0.55	0.53	0.55	0.53	0.55	0.53	0.60	0.53	0.53	0.66	0.58	0.58
1/8 EnergyShield™/ 1/8 clear	0.42	0.38	0.42	0.38	0.42	0.38	0.32	0.29	0.29	0.57	0.50	0.50
3/16 EnergyShield™/ 3/16 clear	0.41	0.38	0.41	0.38	0.41	0.38	0.32	0.28	0.28	0.57	0.50	0.50
1/8 EnergyShield Xtreme™/ 1/8 clear	0.42	0.38	0.42	0.38	0.42	0.38	0.24	0.21	0.21	0.51	0.45	0.45
3/16 EnergyShield Xtreme™/ 3/16 clear	0.41	0.38	0.41	0.38	0.41	0.38	0.24	0.21	0.21	0.50	0.44	0.44
1/8 bronze/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.52	0.46	0.46	0.50	0.44	0.44
3/16 bronze/ 3/16 clear	0.55	0.53	0.55	0.53	0.55	0.53	0.46	0.41	0.41	0.43	0.38	0.38
1/4 Solarcool/ 3/16 clear	0.55	0.53	0.55	0.53	0.55	0.53	0.26	0.23	0.23	0.15	0.13	0.13
1/8 grey/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.48	0.43	0.43	0.45	0.39	0.39
3/16 grey/ 3/16 clear	0.55	0.53	0.55	0.53	0.55	0.53	0.42	0.37	0.37	0.37	0.33	0.33
1/8 greylite # 31/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.27	0.24	0.24	0.18	0.15	0.15
1/8 Azuria/ 1/8 clear	0.56	0.54	0.56	0.54	0.56	0.54	0.40	0.36	0.36	0.57	0.50	0.50
3/16 Azuria/ 3/16 clear	0.55	0.53	0.55	0.53	0.55	0.53	0.35	0.31	0.31	0.53	0.46	0.46
1/8 bronze/ 1/8 EnergyShield™	0.42	0.38	0.42	0.38	0.42	0.38	0.32	0.28	0.28	0.43	0.37	0.37
3/16 bronze/ 3/16 EnergyShield™	0.41	0.38	0.41	0.38	0.41	0.38	0.29	0.26	0.26	0.37	0.32	0.32
1/8 grey/ 1/8 EnergyShield™	0.42	0.38	0.42	0.38	0.42	0.38	0.30	0.27	0.27	0.38	0.34	0.34
3/16 grey/ 3/16 EnergyShield™	0.41	0.38	0.41	0.38	0.41	0.38	0.26	0.24	0.24	0.32	0.28	0.28
1/8 Azuria/ 1/8 EnergyShield™	0.42	0.38	0.42	0.38	0.42	0.38	0.30	0.27	0.27	0.49	0.43	0.43
3/16 Azuria/ 3/16 EnergyShield™	0.41	0.38	0.41	0.38	0.41	0.38	0.28	0.25	0.25	0.46	0.40	0.40
3/16 Solexia/ 3/16 EnergyShield™	0.41	0.38	0.41	0.38	0.41	0.38	0.32	0.29	0.29	0.50	0.44	0.44
DS EnergyShield Xtreme™/ DS ILE	0.36	0.34	0.36	0.34	0.36	0.34	0.23	0.21	0.21	0.49	0.43	0.43
3/16 EnergyShield Xtreme™/ 3/16 ILE	0.36	0.33	0.36	0.33	0.36	0.33	0.23	0.21	0.21	0.49	0.43	0.43

U-Value is the overall coefficient of heat transmittance of heat flow measured in BTU/hr.\* ft<sup>2</sup>\*°F. Lower U-Values indicate better performance. Winter nighttime U-Values are calculated using an outdoor air temperature of 0°F and indoor air temperature of 70°F.

Solar Heat Gain Coefficient is defined that fraction of incident solar radiation that actually enters a building through the window as heat gain. The SHGC is expressed as a dimensionless number from 0 to 1.0 A high coefficient signifies high heat gain, while a low number means low heat gain.

Visible Transmittance is the amount of light in the visible portion of the spectrum that passes through a glazing material. This property does not directly affect heating and cooling loads in a building.

Clear glass - includes all non-tinted pattern glass, i.e. Obscure, Rain, Delta Frost

EnergyShield™ spectrally selective Low-E with emissivity 0.036

EnergyShield Xtreme™ spectrally selective Low-E with emissivity 0.024